

## Trough and mounting fittings PVC



### Description

Installation trough used for air conditioning installation. They allow you to mask cooling lines and condensate drains in an aesthetic way. PVC material in two colours Optimal Duct – pure white and ARTICA DUCT - creamy white. Increased resistance for UV radiation and mechanical damage. Wide temperature range -20°C +60°C.



External corner PVC  
**ODCO 80**  
**CLCO 80**

#### Technical specifications [mm]


| Model   | Width | Height | Quantity in the box [pcs.] |
|---------|-------|--------|----------------------------|
| ODCO 80 | 80    | 60     | 10                         |
| CLCO 80 | 80    | 60     | 10                         |

T-piece PVC  
**ODTJ 80**  
**CLT 80**



#### Technical specifications [mm]

| Model   | Width | Height | Quantity in the box [pcs.] |
|---------|-------|--------|----------------------------|
| ODTJ 80 | 80    | 60     | 10                         |
| CLT 80  | 80    | 60     | 10                         |



Mounting bend PVC  
**ODFE 80**  
**CLFE 80**

#### Technical specifications [mm]

| Model   | Width | Height | Quantity in the box [pcs.] |
|---------|-------|--------|----------------------------|
| ODFE 80 | 80    | 60     | 10                         |
| CLFE 80 | 80    | 60     | 10                         |

Rosette  
**ODWR 80**  
**CLFR 80**



#### Technical specifications [mm]

| Model   | Width | Height | Quantity in the box [pcs.] |
|---------|-------|--------|----------------------------|
| ODWR 80 | 80    | 60     | 10                         |
| CLFR 80 | 80    | 60     | 10                         |